

INTERNATIONAL OPTIMIST CLASS

Sail Measurement Form

Only page 1 need be completed if the Optimist has not yet been allocated a sail number.


Sailmaker's name: J SAIL Date manufactured: 9.12.13
 Sail button number: 79057 Date measured: 13.12.13
 Owner's Name: ANAN YA CHODHAN

Measurer's Name IN BLOCK CAPITALS: PIA KLKOWSKI ANDRZEJ

Sails must be measured by an independent measurer (See CR 2.5.3)

- Notes: 1. The measurer shall enter the actual measurements in the boxes where appropriate.
 2. If the sail complies with all the requirements, the measurer shall sign and date it.
 3. Cross out OK / Not OK as required.

ITEM	Dimension no [as per rule 6.4]	MEASUREMENT	Min. (mm)	Actual (mm)	Max. (mm)
1	2	Head length		1234	1240
2	6	Luff length		1724	1730
3	9	Upper edge of luff measurement band to throat point		596	600
4	8	Length of luff measurement band	60	70	
5	7	Width of luff measurement band	5	5	
6	3	Diagonal	2450	2553	2580
7	1	Leech length		2795	2800
8	22	Peak point to intersection of leech and lower corner of lowermost batten pocket	1850	1877	1950
9	21	Peak point to intersection of leech and lower corner of uppermost batten pocket	900	905	1000
10	25	Deviation from straight line between lower corner of lower batten pocket and clew point	-10	0	5
11	24	Deviation from straight line between lower corner of top batten pocket and upper corner of lower batten pocket	-10	0	5
12	26	Deviation from straight line between the lower corner of the upper batten pocket and clew point	-5	0	20
13	23	Deviation from straight line between peak point and upper corner of upper batten pocket	-10	0	5
14		Half Luff point to half leech point			
15	4	Item 14 plus positive value of any negative deviation in Item 11		1697	1700
16	19	Batten pocket length (outside)		Both OK / Not OK	460
17	20	Batten pocket width (outside)		Both OK / Not OK	40
18	14	Flutter patches		OK	150
19	11	Primary reinforcements from corner measurement points		All OK / Not OK	205
20	12	Secondary reinforcements from corner measurement points		All OK / Not OK	615
21	13	Batten pocket patches at each end of batten pockets		Both OK / Not OK	150
22	15	Tabling width		All OK / Not OK	40
23	16	Seam width		All OK / Not OK	15
24	10	Thickness of woven ply anywhere in the body of the sail	0.15	0.16	
25	17	Trapezoidal window opening area		0.08	0.1 m2
26	18	Shortest distance from window to any edge of sail	150	215	
27	27	Space between foot eyelets	230	All OK / Not OK	260
28	28	Space between foot eyelets	270	All OK / Not OK	300



Measurer's signature: [Signature] Date: 13.12.13 Measurer recognised by: P22

Sail Measurement Form

National Letters and Sail Numbers

Only page 1 need be completed if the Optimist has not yet been allocated a sail number.

SAIL NUMBER: 1396

- Notes:
1. The measurer shall enter the actual measurements in the boxes where appropriate.
 2. If the sail complies with all the requirements, the measurer shall sign and date it.
 3. Cross out OK / Not OK as required.

ITEM	Dimension no [as per rule 6.5.1]	MEASUREMENT	Min. (mm)	Actual (mm)	Max. (mm)
1	1	Height	230	All OK / Not OK	240
2	2	Width (except "1" or "l")	150	All OK / Not OK	160
3	3	Width for M and W	160	All OK / Not OK	170
4	4	Thickness	30	All OK / Not OK	40
5	5	Space between adjoining numbers or letters	40	All OK / Not OK	50
6	6	Space between rows of numbers or letters	40	All OK / Not OK	50
7	7	Space between the national letter groups on opposite sides of the sail	100		150
8	8	Distance between the luff and the closest letter or number in each row	150		
9	9	Distance between lower edge of uppermost batten pocket and the national letter which is closest to the leech	40		50
10	RRS G1.2(b)	Minimum space between characters and edge of sail (leech)	45	All OK / Not OK	

Measurer's Name IN BLOCK CAPITALS: _____

Sails must be measured by an independent measurer (See CR 2.5.3)

Measurer's signature: _____ Date: _____ Measurer recognised by: _____

Second Measurement

If the sail letters/number is changed

SAIL NUMBER: _____

Owner's Name: _____

ITEM	Dimension no [as per rule 6.5.1]	MEASUREMENT	Min. (mm)	Actual (mm)	Max. (mm)
1	1	Height	230	All OK / Not OK	240
2	2	Width (except "1" or "l")	150	All OK / Not OK	160
3	3	Width for M and W	160	All OK / Not OK	170
4	4	Thickness	30	All OK / Not OK	40
5	5	Space between adjoining numbers or letters	40	All OK / Not OK	50
6	6	Space between rows of numbers or letters	40	All OK / Not OK	50
7	7	Space between the national letter groups on opposite sides of the sail	100		150
8	8	Distance between the luff and the closest letter or number in each row	150		
9	9	Distance between lower edge of uppermost batten pocket and the national letter which is closest to the leech	40		50
10	RRS G1.2(b)	Minimum space between characters and edge of sail (leech)	45	All OK / Not OK	

Measurer's Name IN BLOCK CAPITALS: _____

Sails must be measured by an independent measurer (See CR 2.5.3)

Measurer's signature: _____ Date: _____ Measurer recognised by: _____